

# Mathematics 2130

## Project 2

### Approximating $\pi$

The constant  $\pi$ , used to represent the ratio between the circumference of a circle and its diameter, has a long and interesting history. By about 2000 BCE, the Babylonians and the Egyptians had discovered the constancy of this ratio. The Babylonians used  $\frac{25}{8}$  as an approximation to it, while the Egyptians estimated it to be  $4 \cdot (\frac{8}{9})^2$ . Subsequently, the more accurate value  $\frac{22}{7}$  came to be used for  $\pi$ . Over the years, that value was refined to a considerable extent; nowadays, algorithms for computing (millions of) digits of  $\pi$  remain a standard benchmarking tool for testing new computer architectures. But interesting algorithms for computing  $\pi$  were devised long before the age of modern computing.

The purpose of this project is to explore the algorithm developed by the famous scientist and philosopher, Archimedes of Syracuse (287–212 BCE). He described the oldest known algorithm which enables the calculation of  $\pi$  to any desired accuracy — a novel idea for his era!

Given a circle, Archimedes suggested that we **inscribe** a regular  $n$ -sided polygon — called an  $n$ -gon — inside the circle, and use the ratio of the perimeter of the polygon to the diameter as a lower bound for  $\pi$ . At the same time, he suggested that we also **circumscribe** a regular  $n$ -gon about the circle, and use the same calculation to obtain an upper bound for  $\pi$ . By choosing more sides (that is, making  $n$  larger and larger) we can generate more accurate approximations to  $\pi$ .

## Methodology

Archimedes' estimates of  $\pi$  were based on 96-gons. When you consider that he did this with no trigonometry, no systematic means of computing square roots, and without even a decimal number system, the feat becomes even more remarkable.

Find a regular hexagon (a 6-gon) inscribed in the unit circle centred at the origin of a standard two-dimensional coordinate system. Calculate the length of each side of the hexagon and thereby compute a lower bound for  $\pi$ .

To proceed to larger values of  $n$ , imagine that the sides of the hexagon are rubber bands. To construct a 12-gon from a 6-gon, grab the midpoint of each of the hexagon's sides and pull those midpoints to the circle boundary in the centrifugal direction. We now have a dodecagon inscribed in the circle. What is the length of each side of this dodecagon? If you label a side of the hexagon  $\ell_6$  and a side of the dodecagon  $\ell_{12}$ , then you can derive a formula for  $\ell_{12}$  in terms of  $\ell_6$  using only the basic arithmetic operators  $+$ ,  $-$ ,  $\times$ ,  $\div$ ,  $\sqrt{\quad}$ . In fact, all you need here is the theorem of Pythagoras. After you do this, it should be clear how to proceed in an iterative fashion, so that you can determine the length of the sides of a regular 24-gon, then a 48-gon, and so on. Upper bounds to  $\pi$  can be obtained in an analogous way, using circumscribed polygons.

Archimedes started with a hexagon because, although he had no trigonometry, he knew that in a 30-60-90 triangle, the ratio of the short side to the hypotenuse is always  $\frac{1}{2}$ , that

is,  $\sin\left(\frac{\pi}{6}\right) = 0.5$ . (A means of computing square roots was required and none was available. Like any good mathematician, he made one up!)

You may also start with an inscribed pentagon (a 5-gon) using the (less known) fact that

$$\cos\left(\frac{\pi}{5}\right) = \frac{1 + \sqrt{5}}{4}.$$

In this approach, you will compute the perimeters of inscribed and circumscribed decagons (10-gons), 20-gons,  $\dots$ ,  $n$ -gons obtained by the iteration, as explained above. Or you could start with an inscribed square (a 4-gon) and utilise inscribed octagons (8-gons), 16-gons, and so on.

One of the tasks in this project is to write a computer program that will implement Archimedes' algorithm. Your program should include the following ingredients:

- The user should be asked for an initial value of  $n = n_0$  (where  $n_0$  is amongst a list of appropriate values). The program should then determine an estimate for  $\pi$  based on the perimeters of inscribed and circumscribed  $n$ -gons.
- Proceed to polygons with  $n_1 = 2n_0$  sides, then polygons with  $n_2 = 4n_0$  sides, and so on, up to a number of sides equal to  $n_m = 2^m n$ , where  $m$  is another user-inputted value. To reflect some of Archimedes' limitations, your program should only employ the basic arithmetic operators  $+$ ,  $-$ ,  $\times$ ,  $\div$ ,  $\sqrt{\quad}$ . **Trigonometric functions must not be used in your program, nor in the development of the mathematics underlying it.**

After your program is working well, investigate how fast the difference between the upper and lower bounds decreases as  $n$  gets larger. Also, find out how fast these values approximate a high-precision value of  $\pi$  found elsewhere.

In the year 264 CE, a Chinese scholar named Liu Hui estimated  $\pi = 3.14159$  using a 3072-gon (unaware that Archimedes had already invented the same algorithm 400 years earlier). Can you verify the accuracy of his calculation? How many sides would be required to obtain ten-digit accuracy?

Episodes like this from the history of  $\pi$  will make great material for your report! Furthermore, suitable graphics are essential. Describe the mathematical details of your implementation of Archimedes' algorithm along with a list of upper and lower bounds based on sample values of  $n$ .